

Safety Data Sheet



according to OSHA Hazard Communication
29 CFR Part 1910.1200

according to Regulation (EC)
No. 1907/2006 Article 31

Section 1. Identification

Product Code: 882002

Product Name: TM LF YEL HYD BC2002

Product Type: Thermoplastic

Recommended Use: Traffic Markings

Supplied by: Ennis-Flint
A Traffic Safety Solutions Company
115 Todd Court
Thomasville, NC 27360
T: 800.331.8118 (For Technical Inquiries)

Emergency Telephone: Chemtrec 1-800-424-9300

Section 2. Hazard(s) identification

EMERGENCY OVERVIEW: This product contains a component suspected of causing cancer. However, it is in a non-respirable form and inhalation is unlike to occur from exposure. This classification is relevant when exposed to dust or powder form only (e.g. sanding, grinding).

Classification

Symbol(s) of Product



Signal Word

Warning

GHS Named Chemicals On Label

Crystalline Silica, Quartz

GHS HAZARD STATEMENTS

Carcinogenicity, category 2	H351	Suspected of causing cancer.
STOT, repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.

GHS PRECAUTIONARY STATEMENTS

P201	Obtain special instructions before use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P281	Use personal protective equipment as required.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.

Section 3. Composition/Information on ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Crystalline Silica, Quartz	14808-60-7	10-25	GHS08	H351-373
Titanium Dioxide	13463-67-7	0.1-1.0	GHS08	H351

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>EINECS No.</u>	<u>REACH Reg No.</u>	<u>M-Factors</u>
Crystalline Silica, Quartz	14808-60-7	238-878-4	not available	0
Titanium Dioxide	13463-67-7	236-675-5	not available	0

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

Section 4. First-aid measures



FIRST AID - INHALATION: Move to fresh air. Consult a physician if symptoms persist.

FIRST AID - SKIN CONTACT: In case of BURNS, remove patient from heat source. Immediately cool affected skin for as long as possible with cold water. Remove smoldering clothing, including shoes, boots and jewelry unless adhering to skin. Do not remove clothing if adhering to skin. Do not attempt to remove the molten thermoplastic from the skin. Removal could result in severe tissue damage. Cover patient with dry clean sheet. Conduct primary survey. If indicated, transport patient to emergency treatment facility. Wash affected area immediately with soap and plenty of water. Remove contaminated clothing and launder before reuse. Consult a physician if symptoms persist.

FIRST AID - EYE CONTACT: Contact with molten materials requires immediate medical assistance. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult a physician if symptoms persist.

FIRST AID - INGESTION: Do NOT induce vomiting. If conscious, rinse mouth and drink plenty of water. Never give anything by mouth to an unconscious person. Consult a physician.

Section 5. Fire-fighting measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: None expected.

SPECIAL FIREFIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

Section 6. Accidental release measures

ENVIRONMENTAL PRECAUTIONS: Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Use personal protective equipment. Ensure adequate ventilation. Dike far ahead of liquid spill for later disposal. Soak up with inert absorbent material. Take up mechanically. Keep in suitable and closed containers for disposal. Avoid dust formation. Cover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry.

Section 7. Handling and storage



HANDLING: Ensure adequate ventilation. Avoid breathing vapor, mists or dust. Avoid contact with eyes, skin, and clothing. Wear appropriate personal protective equipment. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Observe good industrial hygiene practices. Avoid dust formation. Fine dust dispersed in air may ignite. Do not reheat product packaged in light metal containers. The light metal containers will not safely support the movement or transfer of the product in a hot, molten form. Do not heat over 260°C/500°F in a closed container. This product when heated to above 260°C/500°F can lead to flashing. Appropriate protective equipment must be worn when mixing and applying this product. Keep away from heat and sources of ignition. The thermoplastic bag can be hazardous when empty, because it can retain product residue. Therefore do not reuse container for food, clothing, or products for human or animal consumption or where skin contact may occur. Always obey hazard warnings and handle containers as if they were full. The meltable bag is compatible with the thermoplastic allowing them to melt and become part of the hot melt mixture at application temperature.

STORAGE: Keep container tightly closed in a dry and well-ventilated place. Keep in properly labeled containers.

Section 8. Exposure controls/personal protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Crystalline Silica, Quartz	0.025 mg/m3		0.05 mg/m3	
Titanium Dioxide	10 mg/m3		15 mg/m3	

<u>Name</u>	<u>Percentage</u>	<u>VME mg/m3</u>	<u>VME ppm</u>	<u>OEL Nota</u>
Titanium Dioxide	< 1.0	10	0	15 mg/m3

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation
Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.



SKIN PROTECTION: Protective gloves/clothing. Use of long sleeved shirts is required when handling molten material.



EYE PROTECTION: Safety glasses with side-shields. Use of a faceshield is recommended when handling molten material.



OTHER PROTECTIVE EQUIPMENT: Eyewash stations, safety showers, ventilation systems.



HYGIENIC PRACTICES: When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

Section 9. Physical and chemical properties

Appearance:	yellow	Physical State:	Solid
Odor:	Odorless	Odor Threshold:	Not Established
Density, g/cm3:	1.900	pH:	NI
Freeze Point, °C:	NI	Viscosity:	NI
Solubility in Water:	Not soluble	Partition Coefficient, n-octanol/ water:	NI
Decomposition Temp., °C:	NI		
Boiling Point, °C:	N.I.	Explosive Limits, vol%:	N.I.
Combustibility:	Does not Support Combustion	Flash Point, °C:	>260
Evaporation Rate:	Slower than Diethyl Ether	Auto-ignition Temp., °C:	NI
Vapor Density:	Heavier than air	Vapor Pressure:	NI

(See "Other information" Section for abbreviation legend)

Section 10. Stability and reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Dust formation. Dust may form explosive mixture in air. Heat, flames and sparks.

INCOMPATIBILITY: None known based on information supplied.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon oxides. Nitrogen oxides.

HAZARDOUS POLYMERIZATION: Hazardous polymerization does not occur.

Section 11. Toxicological information



Practical Experiences

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation of dust in high concentration may cause irritation of respiratory system. In molten state, the material does not give off fumes that are toxic or injurious to persons or property. However, excessive inhalation of vapors in molten state can cause nose and throat irritation, may cause nervous system depression characterized by headache, dizziness, nausea, staggering gait, confusion and unconsciousness.

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Direct skin contact may cause irritation. The molten product can cause serious burns.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Direct eye contact may cause irritation. The molten product can cause serious burns.

EFFECT OF OVEREXPOSURE - INGESTION: Ingestion may cause irritation to mucous membranes.

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product. Inhalation exposure to respirable levels of crystalline silica may cause respiratory impairment and lung damage. This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen.

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name according to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Gas LC50</u>
14808-60-7	Crystalline Silica, Quartz	>2000 mg/kg	> 2000 mg/kg	>20001 ppm
13463-67-7	Titanium Dioxide	> 10000 mg/kg rat	> 10000 mg/kg rabbit	>20001 ppm

N.I. - No Information

Section 12. Ecological information

ECOLOGICAL INFORMATION: The environmental impact of this product has not been fully investigated.

Further Ecological Information

Contains the following ingredients which are classified as water dangerous according to EEC directive No. 76/464/EEC in percentages > 1%.

<u>CAS-No.</u>	<u>Name according to EEC</u>	<u>Bio. Conc. Factor (BCF)</u>	<u>Octanol-water par. Coeff (KOW)</u>
14808-60-7	Crystalline Silica, Quartz	not available	not available
13463-67-7	Titanium Dioxide	not available	not available

Section 13. Disposal considerations



Product

DISPOSAL METHOD: This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). Dispose of contents/ container in accordance with the local/regional/national/international regulations. Do not re-use empty containers.

European Waste Code: 080201 waste coating powder

Uncleaned Packaging

European Waste Code: 150110 packaging dangerous residuals

Section 14. Transport information

SPECIAL TRANSPORT PRECAUTIONS: When in use, this product is elevated temperature liquid, n.o.s. (compound pavement marking), UN3257, Hazard Class 9, Packing Group III.

Road Transport

UN Number:	Not regulated
ADR/RID Class:	Not regulated
Packing Group:	No Information
Shipping Name:	Not regulated
Primary Shipping Hazard:	No Information
Road Tunnel Transport Code:	Not regulated

Sea Transport

UN Number:	Not regulated
IMDG/GGVSee Class:	Not regulated
EmS-No:	Not regulated
Packing Group:	No Information
Shipping Name:	Not regulated
Primary Shipping Hazard:	No Information
Marine Pollutant:	Not A Marine Pollutant
Shipping Hazard(Marine Pollutant):	No Information

Air Transport

UN Number:	Not regulated
ICAO/IATA Class:	Not regulated
Packing Group:	No Information
Shipping Name:	Not regulated
Primary Shipping Hazard:	No Information

Section 15. Regulatory information**U.S. Federal Regulations:****CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Health Hazard, Chronic Health Hazard

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

<u>Chemical Name</u>	<u>CAS-No.</u>
Crystalline Silica, Quartz	14808-60-7
Titanium Dioxide	13463-67-7
Silicon dioxide, amorphous	7631-86-9

U.S. State Regulations:**NEW JERSEY RIGHT-TO-KNOW:**

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
Calcium Carbonate	1317-65-3
Silicon Dioxide	99439-28-8
Petroleum Hydrocarbon Resin	64742-16-1

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
Calcium Carbonate	1317-65-3
Silicon Dioxide	99439-28-8
Petroleum Hydrocarbon Resin	64742-16-1
Low Density Polyethylene Wax	9002-88-4

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

<u>Chemical Name</u>	<u>CAS-No.</u>
Crystalline Silica, Quartz	14808-60-7
Titanium Dioxide	13463-67-7

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations: As follows -**CANADIAN WHMIS:**

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class: D2A

Denmark

B-Value: 0.000000

France

Storage Conditions: No Information

Professional Illness Table:

<u>CAS Number</u>	<u>Chemical Name</u>	<u>Professional Illness</u>
14808-60-7	Crystalline Silica, Quartz	not available
13463-67-7	Titanium Dioxide	not available

Germany

VbF-Class: No Information

WGK-class: 0

Remarks: WGK 0 = in general not a water pollutant
WGK 1 = weak water pollutant
WGK 2 = water pollutant
WGK 3 = severe water pollutant

Processing restrictions:***Incident Regulation:**

No Information

Spain

Storage Conditions: No Information

Switzerland

VOC-Value: 0.00

United Kingdom

Storage Conditions: No Information

Section 16. Other information, including date of preparation of the last revision

Revision Date: 5/24/2016 Supercedes Date: 4/1/2016

Reason for revision: Statement(s) Changed

Datasheet produced by: Regulatory Department

HMIS Ratings:

Health:	1	Flammability:	1	Reactivity:	0	Personal Protection:	X
---------	---	---------------	---	-------------	---	----------------------	---

NFPA Ratings:

Health:	1	Flammability:	1	Reactivity:	0	Hazards:	N.I.
---------	---	---------------	---	-------------	---	----------	------

Volatile Organic Compounds, gr/ltr: 0

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed. Any use of the product not in conformance with this SDS or in combination with any other product or process is the responsibility of the user.