Safety Data Sheet



according to OSHA Hazard Communication 29 CFR Part 1910.1200

according to Regulation (EC) No. 1907/2006 Article 31

Section 1. Identification

Product Code:

884655

Product Name:

TM LF YEL HYD AASHTO EXTRD

Product Type:

Thermoplastic

Recommended Use:

Traffic Markings

Supplied by:

Ennis-Flint

A Traffic Safety Solutions Company

115 Todd Court

Thomasville, NC 27360

T: 800.331.8118 (For Technical Inquiries)

Emergency Telephone:

Chemtrec

1-800-424-9300

Section 2. Hazard(s) identification

EMERGENCY OVERVIEW: This product contains a component suspected of causing cancer. However, it is in a non-respirable form and inhalation is unlike to occur from exposure. This classification is relevant when exposed to dust or powder form only (e.g. sanding, grinding).

Classification

Symbol(s) of Product



Signal Word

Warning

GHS Named Chemicals On Label

Titanium Dioxide

GHS HAZARD STATEMENTS

Carcinogenicity, category 2

H351

Suspected of causing cancer.

GHS PRECAUTIONARY STATEMENTS

P201

Obtain special instructions before use.

P281

Use personal protective equipment as required.

P308+P313

IF exposed or concerned: Get medical advice/attention.

Section 3. Composition/Information on ingredients

Chemical Name

CAS-No.

Wt. % GHS Symbols

GHS Statements

Titanium Dioxide

13463-67-7

1.0-2.5

GHS08 F

Crystalline Silica, Quartz

14808-60-7

0.1-1.0 GHS08

H351-373

Chemical NameCAS-No.EINECS No.REACH Reg No.M-FactorsTitanium Dioxide13463-67-7236-675-5not available0Crystalline Silica, Quartz14808-60-7238-878-4not available0

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

Section 4. First-aid measures



FIRST AID - INHALATION: Move to fresh air. Consult a physician if symptoms persist.

FIRST AID - SKIN CONTACT: In case of BURNS, remove patient from heat source. Immediately cool affected skin for as long as possible with cold water. Remove smoldering clothing, including shoes, boots and jewelry unless adhering to skin. Do not remove clothing if adhering to skin. Do not attempt to remove the molten thermoplastic from the skin. Removal could result in severe tissue damage. Cover patient with dry clean sheet. Conduct primary survey. If indicated, transport patient to emergency treatment facility. Wash affected area immediately with soap and plenty of water. Remove contaminated clothing and launder before reuse. Consult a physician if symptoms persist.

FIRST AID - EYE CONTACT: Contact with molten materials requires immediate medical assistance. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult a physician if symptoms persist.

FIRST AID - INGESTION: Do NOT induce vomiting. If conscious, rinse mouth and drink plenty of water. Never give anything by mouth to an unconscious person. Consult a physician.

Section 5. Fire-fighting measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: None expected.

SPECIAL FIREFIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

Section 6. Accidental release measures

ENVIRONMENTAL PRECAUTIONS: Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Use personal protective equipment. Ensure adequate ventilation. Dike far ahead of liquid spill for later disposal. Soak up with inert absorbent material. Take up mechanically. Keep in suitable and closed containers for disposal. Avoid dust formation. Cover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry.

Section 7. Handling and storage





HANDLING: Ensure adequate ventilation. Avoid breathing vapor, mists or dust. Avoid contact with eyes, skin, and clothing. Wear appropriate personal protective equipment. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Observe good industrial hygiene practices. Avoid dust formation. Fine dust dispersed in air may ignite. Do not reheat product packaged in light metal containers. The light metal containers will not safely support the movement or transfer of the product in a hot, molten form. Do not heat over 260°C/500°F in a closed container. This product when heated to above 260°C/500°F can lead to flashing. Appropriate protective equipment must be worn when mixing and applying this product. Keep away from heat and sources of ignition. The thermoplastic bag can be hazardous when empty, because it can retain product residue. Therefore do not reuse container for food, clothing, or products for human or animal consumption or where skin contact may occur. Always obey hazard warnings and handle containers as if they were full. The meltable bag is compatible with the thermoplastic allowing them to melt and become part of the hot melt mixture at application temperature.

STORAGE: Keep container tightly closed in a dry and well-ventilated place. Keep in properly labeled containers.

Section 8. Exposure controls/personal protection

Ingredients with Occupational Exposure Limits

Chemical Name ACGIH TLV-TWA ACGIH-TLV STEL OSHA PEL-TWA OSHA PEL-CEILING

Titanium Dioxide 10 mg/m3 15 mg/m3
Crystalline Silica, Quartz 0.025 mg/m3 0.05 mg/m3

Name Percentage VME mg/m3 VME ppm OEL Nota

Titanium Dioxide 1.0-2.5 10 0 15 mg/m3

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.



SKIN PROTECTION: Protective gloves/clothing. Use of long sleeved shirts is required when handling molten material.



EYE PROTECTION: Safety glasses with side-shields. Use of a faceshield is recommended when handling molten material.



OTHER PROTECTIVE EQUIPMENT: Eyewash stations, safety showers, ventilation systems.



HYGIENIC PRACTICES: When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

Section 9. Physical and chemical properties

Appearance: vellow Physical State: Solid

Odor: Odorless Odor Threshold: Not Established

Density, g/cm3: 1.750 pH: NI
Freeze Point, °C: NI Viscosity: NI

Solubility in Water: Not soluble Partition Coefficient, n-octanol/ NI

Decomposition Temp., °C: NI water:

Boiling Point, °C: N.I. Explosive Limits, vol%: N.I.

Combustibility: Does not Support Combustion Flash Point, °C: >260

Evaporation Rate: Slower than Diethyl Ether Auto-ignition Temp., °C: NI

Vapor Density: Heavier than air Vapor Pressure: NI

(See "Other information" Section for abbreviation legend)

Section 10. Stability and reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Dust formation. Dust may form explosive mixture in air. Heat, flames and sparks.

INCOMPATIBILITY: None known based on information supplied.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon oxides. Nitrogen oxides.

HAZARDOUS POLYMERIZATION: Hazardous polymerization does not occur.

Section 11. Toxicological information



Practical Experiences

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation of dust in high concentration may cause irritation of respiratory system. In molten state, the material does not give off fumes that are toxic or injurious to persons or property. However, excessive inhalation of vapors in molten state can cause nose and throat irritation, may cause nervous system depression characterized by headache, dizziness, nausea, staggering gait, confusion and unconsciousness.

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Direct skin contact may cause irritation. The molten product can cause serious burns.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Direct eye contact may cause irritation. The molten product can cause serious burns.

EFFECT OF OVEREXPOSURE - INGESTION: Ingestion may cause irritation to mucous membranes.

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product. Inhalation exposure to respirable levels of crystalline silica may cause respiratory impairment and lung damage. This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen.

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name according to EEC	Oral LD50	Dermal LD50	Gas LC50
13463-67-7	Titanium Dioxide	> 10000 mg/kg rat	> 10000 mg/kg rabbit	>20001 ppm
14808-60-7	Crystalline Silica, Quartz	>2000 mg/kg	> 2000 mg/kg	>20001 ppm

N.I. - No Information

Section 12. Ecological information

ECOLOGICAL INFORMATION: The environmental impact of this product has not been fully investigated.

Further Ecological Information

Contains the following ingredients which are classified as water dangerous according to EEC directive No. 76/464/EEC in percentages > 1%.

CAS-No.	Name according to EEC	Bio. Conc. Factor (BCF)	Octanol-water par. Coeff (KOW)
13463-67-7	Titanium Dioxide	not available	not available
14808-60-7	Crystalline Silica, Quartz	not available	not available

Section 13. Disposal considerations



Product

DISPOSAL METHOD: This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). Dispose of contents/ container in accordance with the local/regional/national/international regulations. Do not re-use empty containers.

European Waste Code: 080201 waste coating powder

Uncleaned Packaging

European Waste Code: 150110 packaging dangerous residuals

Section 14. Transport information

SPECIAL TRANSPORT PRECAUTIONS: When in use, this product is elevated temperature liquid, n.o.s. (compound pavement marking), UN3257, Hazard Class 9, Packing Group III.

Road Transport

UN Number:
ADR/RID Class:
Not regulated
Packing Group:
No Information
Shipping Name:
Primary Shipping Hazard:
Road Tunnel Transport Code:
Not regulated
Not regulated
Not regulated

Sea Transport

UN Number:
IMDG/GGVSee Class:
Not regulated
Not regulated
Packing Group:
No Information
Shipping Name:
Not regulated
No Information

Marine Pollutant: Not A Marine Pollutant

Shipping Hazard(Marine Pollutant):

No Information

Air Transport

UN Number:
ICAO/IATA Class:
Packing Group:
Not regulated
No Information
Not regulated
No Information
Not regulated
Primary Shipping Hazard:
No Information

Section 15. Regulatory information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Health Hazard, Chronic Health Hazard

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

Chemical NameCAS-No.Titanium Dioxide13463-67-7Crystalline Silica, Quartz14808-60-7Silicon dioxide, amorphous7631-86-9

U.S. State Regulations:

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

 Chemical Name
 CAS-No.

 Calcium Carbonate
 1317-65-3

 Silicon Dioxide
 99439-28-8

 Petroleum Hydrocarbon Resin
 64742-16-1

Pentaerythritol Ester of Rosin

8050-26-8

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

 Chemical Name
 CAS-No.

 Calcium Carbonate
 1317-65-3

 Silicon Dioxide
 99439-28-8

 Petroleum Hydrocarbon Resin
 64742-16-1

 Pentaerythritol Ester of Rosin
 8050-26-8

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

Chemical NameCAS-No.Titanium Dioxide13463-67-7Crystalline Silica, Quartz14808-60-7

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations: As follows -

CANADIAN WHMIS:

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class: D2A

Denmark

B-Value: 0.000000

France

Storage Conditions: No Information

Professional Illness Table:

CAS NumberChemical NameProfessional Illness13463-67-7Titanium Dioxidenot available14808-60-7Crystalline Silica, Quartznot available

Germany

VbF-Class: No Information

WGK-class: 0

Remarks: WGK 0 = in general not a water pollutant

WGK 1 = weak water pollutant WGK 2 = water pollutant WGK 3 = severe water pollutant

Processing restrictions:*

Incident Regulation:

No Information

Spain

Storage Conditions: N

No Information

Switzerland

VOC-Value:

0.00

United Kingdom

Storage Conditions:

No Information

Section 16. Other information, including date of preparation of the last revision

Revision Date:

5/24/2016

Supercedes Date:

4/1/2016

Reason for revision:

Statement(s) Changed

Datasheet produced by:

Regulatory Department

HMIS Ratings:

Health: 1 Flammability: 1 Reactivity: 0 Personal Protection: X

NFPA Ratings:

Health: 1 Flammability: 1 Reactivity: 0 Hazards: N.I.

Volatile Organic Compounds, gr/ltr:

0

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H351

Suspected of causing cancer.

H373

May cause damage to organs through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed. Any use of the product not in conformance with this SDS or in combination with any other product or process is the responsibility of the user.